

ARMARIO EUROSNAACK

ARMARIO REFRIGERACIÓN Y MANTENIMIENTO CONGELADOS AEP-55 /
EUROSNAACK CABINET, CHILLER AND FREEZER AEP-55



CARACTERÍSTICAS GENERALES

- Exterior en acero inox AISI-304 18/10, excepto el respaldo
- Interior en acero inox AISI-304 18/10, con aristas curvas y fondo embutido
- Puertas de apertura reversible, con sistema de cierre automático y burlete magnético (permanece abierta al superar los 90° de apertura)
- Contrapuerta inox embutida
- Luz interior
- Estantes interiores de varilla en acero plastificado, regulables en altura
- Pies en tubo de acero inox ajustables en altura 125-200 mm
- Cuadro de mandos y rejilla ventilación motor, desmontables
- Unidad condensadora ventilada
- Evaporador sistema tiro forzado, con recubrimiento anticorrosión
- Paro ventiladores tiro forzado al abrir la puerta
- Evaporación automática del agua de descarche
- Aislamiento de poliuretano inyectado, densidad 40 Kg/m³, bajo GWP y cero efecto ODP
- Control digital de temperatura y descarches, eficiente en la gestión del consumo de energía
- Temperatura de trabajo a 32°C ambiente


GENERAL FEATURES

- AISI-304 18/10 stainless steel exterior, except the rear side
- AISI-304 18/10 stainless steel interior, stamped bottom and rounded corners
- Doors with self closing system, blocked opening, magnetic gasket and possibility of changing the opening sense
- Rear-door by stamped steel
- Interior lighting
- Shelves made of plasticized steel wire, height adjustable
- AISI-304 18/10 adjustable legs, 125 to 200 mm
- Control panel and engine ventilation grill, removable
- Fan assisted condenser unit
- Fan assisted evaporator, with anticorrosion coating
- Evaporator fan stops when door is opened
- Automatic evaporation of defrost water
- 40 Kg/m³ density polyurethane insulation, low GWP and zero ODP effect
- Energy efficient digital controller of temperature and defrosts
- Operating temperature 32°C ambient


Características técnicas y constructivas sujetas a variación sin previo aviso, todas las fotos deben ser consideradas como una referencia
Technical and constructive characteristics subject to variation without prior notice, all photos must be considered as a reference

ARMARIO EUROSNAACK

ARMARIO REFRIGERACIÓN Y MANTENIMIENTO CONGELADOS AEP-55 /
EUROSNAACK CABINET, CHILLER AND FREEZER AEP-55



AEP-55



AEP-55-7

Modelo Model Modèle	Largo Length Longueur mm	Alto Height Hauteur mm	Fondo Depth Profondeur mm	Rango Range Gamme	Estantes Shelves Étagères	Cajas pescado Fish boxes Boîtes poissons	Pares de guías Sets of slides Kit de guides	Capacidad Capacity Exposition L	Voltaje Voltage Tension	Refrig. Coolant Frigorigène	Potencia Frig. Frig Power Puissance Frig. W	Consumo Nominal Nominal Consumption Consommation Nominale W	Rango Range Gamme	CCE EEC 2015/1094 EN16825	clase climate 2015/1094 EN16825 Rango Range Gamme
AEP-55-7	540	2075	730	-5°C -1°C	0	7	7	409	230 V - 50 Hz	R-290	303	201	-		5 (40°C 40%)
AEP-55-20	540	2075	730	0°C +8°C	3	0	17	409	230 V - 50 Hz	R-290	303	201	E		5 (40°C 40%)
AEP-55-E-20	540	2075	730	0°C +8°C	3	0	17	409	230 V - 50 Hz	R-290	303	213	-		4 (30°C 55%)
AEPC-55-20	540	2075	730	-20°C -15°C	3	0	17	409	230 V - 50 Hz	R-290	495	474	E		4 (30°C 55%)
AEPC-55-E-20	540	2075	730	-20°C -15°C	3	0	17	409	230 V - 50 Hz	R-290	495	485	-		4 (30°C 55%)

Características técnicas y constructivas sujetas a variación sin previo aviso, todas las fotos deben ser consideradas como una referencia
Technical and constructive characteristics subject to variation without prior notice, all photos must be considered as a reference